

## LATICRETE 8510 Bonding Admix



### Concentrated Acrylic Admix

#### PRODUCT DESCRIPTION

LATICRETE 8510 Bonding Admix is a concentrated acrylic admix for use with portland cement mixes, dramatically improving their workability and physical properties. For conventional mortar beds, dry-set mortars and portland cement grouts.

#### USES

- Crack resistant, weather resistant pool plaster
- High strength, weather resistant concrete repair mortars
- High strength masonry mortar
- Fortifier for thin-set mortars to increase bond strength and flexibility
- Anti-rust protection
- Primer

#### ADVANTAGES

- High Strength– improves adhesion, bond and compressive strength of all portland cement mixes
- Economical– super concentrated
- Versatile– one product for interior and exterior installations
- No Damp Curing– cures even in dry climates



### TECHNICAL DATA AT 23°C e 50% U.R.\*



This product has been certified for Low Chemical emissions (ULCOM/GG UL2818) under the UL GREENGUARD Certification Program for Chemical Emissions for Building Materials Finishes and Furnishings (UL2818 Standard) by UL Environment.

Total VOC content is 2.39 g/l

Appearance:	white liquid
Service temperature:	from +5°C to +35°C

#### LATICRETE 8510 Bonding Admix + Cement 42,5

percentage of lattelx on the powder:	33%
working time:	20-25 min.
pH of mixture:	≥ 12
Walkable:	24 ore

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.